

| SHELL Length Code | L Inch (mm)  |            |
|-------------------|--------------|------------|
| -1                | 61.2 (1555)  | (1194)     |
| -1.5              | 81.2 (2063)  | 67 (1702)  |
| -2                | 101.2 (2571) | 87 (2210)  |
| -3                | 141.2 (3587) | 127 (3226) |
| -4                | 181.2 (4603) | 167 (4242) |
| -5                | 221.2 (5619) | 207 (5258) |
| -6                | 261.2 (6635) | 247 (6274) |
| -7                | 301.2 (7651) | 287 (7290) |
| -7.5              | 321.2 (8159) | 307 (7798) |
| -8                | 341.2 (8667) | 327 (8306) |

**TM**

**?**

**±**

11519  
11525  
11513  
11494  
11494  
11494  
11494  
11494  
11494

- 2.DESIGN TEMPERATURE 150°F(65
- 3.MIN ALLOWABLE TEMPERATURE 20°F(-7
- 4.WORKING MEDIUM,WATER pH RANGE 3-10
- 5.PLEASE OPERATE IN ACCORDANCE WITH USER MANUAL
- 6.SPARE PARTS FORM JUST FOR REFERENCE, SPECIFIC FORM OF THE SPARE PART DRAWING PREVAIL
- 7.SUBJECT TO CHANGE WITHOUT NOTICE.

REFERENTIAL PLASTIC SHRINKAGE (IF NECESSARY):

MATERIAL

MODEL WAVE-300P-8  
DESCRIPTION  
300P-8 MEMBRANE HOUSING (Hi-Flo)  
DRAWING NO. | VERSION NO.