

NT

Shell Weight
(kg)

(24202)

(422)

(24400-06)ED40-08-06
(24400-05)ED40-08-05
23300-26
(24300-04)ED25-08-04
(23300-19)EC30-08-19
(23300-18)EC30-08-18
(23300-17)EC30-08-17
(23300-16)EC30-08-16

(23300-03)EC30-08-03
(23450-15)EC45-08-15
(23300-12)EC30-08-12

(23300-08)EC30-08-08
(24300-07)ED25-08-07
(23300-13)EC30-08-13
(23300-14)EC30-08-14
(24400-02)ED40-08-02
(24400-01)ED40-08-01

40246
40255
40425
20132
20119
20067
10175
10180
10188
20123
20123
10141-1
20129
20107
20073
20025
SEE THE CHART
10181
10193
10125
10182
20102

- 2. DESIGN TEMPERATURE 150°F(65)
- 3. MIN ALLOWABLE TEMPERATURE 20°F(-7)
- 4. WORKING MEDIUM WATER pH RANGE 3-10
- 5. PLEASE OPERATE IN ACCORDANCE WITH USER MANUAL
- 6. SPARE PARTS FORM JUST FOR REFERENCE,
SPECIFIC FORM OF THE SPARE PART DRAWING PREVAIL.

FIBER GL

f

M